



**SPOKANE TRIBE OF INDIANS
WELLPINIT BOYS AND GIRLS CLUB REMODEL
WELLPINIT, WA**

ADDENDUM NO. 2
April 30, 2024

This addendum is hereby incorporated into the bidding documents for the Architectural, Civil, Structural, Mechanical and Electrical construction of the above referenced project.

The corrections, clarifications, changes, and approvals herein shall become an integral and binding part of any contract entered into between the Owner, Contractor, and successful sub-bidders.

SPECIFICATIONS

1. Section 11 6623, Gymnasium Equipment.

Add new paragraph 2.10.A. SAFETY PADS

A. Pads.

1. Pad Coverings: Provide safety pad covering that is fabricated from puncture and tear resistant, PVC-coated polyester or nylon reinforced PVC fabric, not less than 14oz./sq. yd. and treated with fungicide for mildew resistance, with surface burning characteristics meeting ASTM 84.

B. Wall Safety Pads:

- a. Padded wall wainscot panels designed to be attached in a continuous row. Each row panel section consists of fill laminated to backer board with visible surfaces fully covered by seamless fabric covering, free of sag and wrinkles and firmly attached to back of backer panel.
- b. Backer Board: Not less than 3/8-inch-thick plywood, mat formed. Or composite panel.
- c. Fill: Manufacturer's standard.
- d. Size: Each panel section, 24 inches wide by not less than 72 inches tall.
- e. Thickness: 3/8 inches.
- f. Number of Panel Sections: Refer to drawings.
- g. Installation Method: Manufacturer's standard.
- h. Fabric Covering Color: As selected by Architect from manufacturer's full range of colors.

C. Cut-out Trim:

- a. Provide manufacturer's standard flanged cut-out trim kits for fitting pads around switches, receptacles, and other obstructions.

APPROVED MANUFACTURER'S SUBSTITUTIONS

ARCHITECTURAL

1. Section 11 6623, Gymnasium Equipment. Paragraph 2.2A, Manufacturer, ADP LEMCO

PLUMBING

1. P0.01 Plumbing Notes, Symbols, & Legends, Grease Trap Interceptor. Manufacturer, Schier

END OF ADDENDUM No. 2